



Booth Coating - Peelable

TECHNICAL DATA SHEET

BENEFITS

- Water base viscous and peelable
- One coating does it all
- When dried resistant to water, alkali and heat
- Non flammable

GENERAL INFORMATION

Water based coating protects against hazardous overspray accumulation. Dries quickly to form a flexible film that can be cleaned of overspray with just soap and water. Easily strips from surface during regular booth maintenance. Can be used on lights, windows and walls.

APPLICATION:

Apply with airless, HVLP or conventional spray equipment. Can also be applied with brush or roller. When applying material over large areas, a 30:1 ratio airless spray unit with a 0.035" fluid orifice in the spray gun will provide good results.

TECHNICAL DATA

Colour:	Available in Clear or White
Viscosity:	10,000 – 15,000 cps
Flash Point:	None
pH:	8.0 – 9.0

Peelable Booth Coating is available in these sizes:

<u>Clear</u>		<u>White</u>	
Part # 20420	20 L pail	Part # 27420	20 L pail
Part # 20445	205 L drum	Part # 27445	205 L drum

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com