



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

FUEL STABILIZER

TECHNICAL DATA SHEET

BENEFITS

- Reduces Wear – Protects and extends the life of fuel pumps, carburetors and injectors
- Versatile – May be used in a variety of equipment including 2 cycle and 4 cycle engines
- Long Lasting – Lasts 12 months or more to stop the degradation of gasoline
- Cleans – Neutralizes sulphur and acids, removes and stops varnish build up, lubricates valve area and removes carbon and gum
- Controls Moisture – Mixes with water and allows the water to burn off, thereby assisting in gas line antifreeze protection in winter

GENERAL INFORMATION

Concentrated fuel additive engineered to address the needs of today's high performance engines and is formulated for current fuel production including fuels containing ethanol. Safe for all engines and contains high performance acid neutralizers, moisture absorption components and selected base oils to achieve superior performance from all grades of fuels.

Fuel Stabilizer may also be used to reduce the formation of gum, varnish and peroxides during the storage of gasoline.

TREATMENT RATE

½ oz per gallon

TECHNICAL DATA

Specific Gravity:	0.8900
Ash Content:	0
Copper Strip Corrosion Test	1a

Fuel Stabilizer is available in these sizes:

Part # 92750	473 mL (16 oz) can
Part # 92704	4 L (1.14 gal) jug
Part # 92720	20 L (5.5 gal) pail

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com