



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

## Loobit – Multipurpose Lubricant and Wire Rope Dressing

TECHNICAL DATA SHEET

### BENEFITS

- User friendly, easy, clean application.
- Health Canada CFIA Listed
- Non flammable as a liquid
- Non solvent, non drying properties for superior lubrication
- WHMIS/OSHA non controlled, environmentally friendly
- Impervious to moisture, salt and most chemicals and gases
- Will not attract dust, dirt and abrasives
- Effective -50°C to high temperatures
- Dielectric strength 34,000 volts
- Inverted spray valve (360°)
- Withstands extreme pressures.
- Compatible with plastic/nylon, rubber, natural materials and all metal alloys.
- Will not cause static electricity.
- Compatible with I.W.R.C. and fibre core wire rope.

### GENERAL INFORMATION

Loobit is a multi use, heavy-duty lubricant, formulated for use on rollers, drive chains, wire rope and cables, internal control cables, open gears, exposed bearings, load bearings, load bearing hinges and pivot points, mechanical controls and more. This superior long lasting lubricant leaves a clear protective film that is always active. Loobit has proven itself superior as a medium viscosity, clean, environmentally friendly wire rope dressing since its introduction more than 60 years ago. Loobit works so well because it lubricates and penetrates under high pressures and extreme fluctuations in temperature. The internal strands within wire rope are lubricated to the core where the lubrication and corrosion protection are required. Loobit displaces moisture. After application Loobit is almost invisible. A random cut cross section of a treated wire rope best exemplifies the advantages of Loobit, as it will reveal a wicking effect with penetration to the core. This benefits in corrosion protection and re-lubrication as the cable twists around pulleys and shives. Metal on metal wear is greatly reduced. Loobit works in the cable not on it. Loobit will not accumulate on cable supports and drive mechanisms.

### TECHNICAL DATA

Flash Point: + 220°C Close cup ASTM D93  
 Pour Point: +90°C  
 Cloud Point: -20°C  
 Viscosity: 400 Cts  
 Dielectric Strength: 34,000 volts

### Loobit is available in these sizes:

Part # 31014	12 x 350 g aerosol	Part # 32045	1 x 205 L drum
Part # 32004	4 x 4 L jug	Part # 33010	12 x 284 mL precision pump
Part # 32016	12 x 455 mL w/trigger sprayer	Part # 38888	12 x Empty 16 oz bottle
Part # 32020	1 x 20 L pail		

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7  
 Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467  
 email: sales@lloydslaboratories.com