



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

Silicone Lubricant

TECHNICAL DATA SHEET

BENEFITS

- Easy to apply
- Safe on all surfaces
- Non toxic and Non staining
- Safe for equipment contacting food products
- Treated surfaces and parts, slide and glide easier without grease
- Not affected by water, oil or most solvents
- Speeds up cleaning of food processing and kitchen equipment
- Stable to heat and cold -40°C to +204°C

GENERAL INFORMATION

Lubricating and preventing sticking, binding and squeaking as well as beautifying, waterproofing and protecting. Use on metal, glass, rubber, plastic, painted finishes, fabrics and on food machinery, automobiles, in manufacturing plants, printing, paper, textile, sewing, food processing and packaging industries.

DIRECTIONS

- Shake can before using
- Spray with container in vertical position and deposit a light film on a previously cleaned surface
- Use a sweeping motion to spray and apply
- Reapply as required

TECHNICAL DATA

Temperature range: -40°C to 204°C
Appearance: Clear colourless liquid
Specific gravity (water=1): 0.64 – 0.66 @20°C
Meets FDA Regulation 21 CFR 175.300 (release agent) and 21 CFR 178.3570 (lubricant, incidental food contact)

Silicone Lubricant is available in these sizes:

Part # 61920 12 x 400 g aerosol

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7

Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467

email: sales@lloydslaboratories.com