

MATERIAL SAFETY DATA SHEET

Lloyds Laboratories Inc.

Rust Paint (Aerosol) Part # 21614

SECTION IV: FIRST AID MEASURES

Eye Contact: Flush with water, lifting upper and lower lids occasionally, then get medical attention.
Skin Contact: Thoroughly wash exposed area with soap and water.
Inhalation:
Ingestion: Induce vomiting if patient is alert. Call a physician or Poison Control Centre immediately.

SECTION V: FIRE FIGHTING MEASURES

Flammability: Non Flammable.
Flash Point deg (C, TCC): 34 – 36.
Means of Extinction: Carbon Dioxide, Dry Chemical, Foam.
Special Fire Hazards: Water from, fogging nozzles may be used to cool closed containers to prevent build-up if exposed to extreme temperatures. Full protective equipment including self contained breathing apparatus should be worn in a fire involving this material.
Auto Ignition Temperature: 245 – 465 °C.
Flame Propagation or Burning Rate of Solid:
Sensitivity to Static Discharge: Not applicable.
Unusual Fire and Explosion Hazards:
Hazardous Decomposition Products: Hydrocarbon fumes and smoke. Carbon Monoxide where combustion is incomplete.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Leak and Spill Procedures: Remove all sources of ignition. Use an inert absorbent material and non-sparking tools. Avoid breathing fumes. Ventilate area. Prevent from entering a water course.

SECTION VII: HANDLING AND STORAGE

Storage Requirements: Keep away from heat, sparks and open flames.

SECTION VIII: EXPOSURE CONTROL/PERSONAL PROTECTION

Gloves: Wear chemical resistant.
Eye Protection: Safety glasses.
Respiratory Protection: If used indoors on a continuous basis, use of a cartridge type respirator (NIOSH/MSHATC 23C or equivalent) is recommended.
Other Protective Equipment: Not required.
Engineering Controls: Ventilation – Local (mechanical if used indoors on a continuous basis.

MATERIAL SAFETY DATA SHEET

Lloyds Laboratories Inc.

Rust Paint (Aerosol) Part # 21614

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (deg C):	100 – 171	Specific Gravity (H ₂ O = 1):	1.20	Evaporation Rate (n-butyl Acetate = 1):	<1
% Volatile (Wt%):	75 - 85	Solubility in water:		pH (as supplied):	8.7 – 9.5
Physical State:	aerosol	Viscosity:		Freezing Point (°C)	<0
Appearance / Odour:	Black liquid with alcohol odour				

SECTION X: STABILITY AND REACTIVITY

Conditions for Chemical Instability: Stable under normal conditions.
Incompatible Materials: Strong oxidizing agents.
Hazardous Decomposition Products: Hydrocarbon fumes and smoke. Carbon Monoxide where combustion is incomplete.

SECTION XI: TOXICOLOGICAL INFORMATION

See Section II for LD50.

SECTION XII: ECOLOGICAL INFORMATION

Information not available.

SECTION XIII: DISPOSAL CONSIDERATIONS

Do not puncture or incinerate containers, even when empty. Dispose of in accordance to all local, provincial/state and federal regulations.

SECTION XIV: TRANSPORTATION

T.D.G. Classification: Consumer Commodity.
D.O.T. Classification:

MATERIAL SAFETY DATA SHEET

Lloyds Laboratories Inc.

Rust Paint (Aerosol) Part # 21614

SECTION XV: REGULATORY INFORMATION

Occupational Health and Safety Regulations:

Toxic Substances Control Act (TSCA):

Canadian Domestic Substance List (DSL):

SECTION XVI: OTHER INFORMATION

Date:	April 15,2016	Prepared By:	Technical Services Group	Telephone:	1 800 361-6766
-------	---------------	--------------	-----------------------------	------------	----------------

Disclaimer:

Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond the control of supplier, it is assumed that users of this material have been fully trained according to the mandatory requirements of WHMIS.

No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries for consequential damages, which may result from the use or reliance on any information contained in this form. If user requires independent information on ingredients in this or other material, we recommend contact with the Canadian Centre of Occupational Health and Safety (CCOHS) in Hamilton, Ontario (905-572-4400 or CSST in Montreal, Quebec (514-873-3990).