



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

DRY FILM LUBRICANT

TECHNICAL DATA SHEET

BENEFITS

- Easy to apply, ready to use
- Dries quickly
- Tenacious, low friction, clean and non oily
- Excellent release characteristics

GENERAL INFORMATION

A clean inert dry film lubricant and release agent. Provides microscopic film forming properties. Teflon has been combined with ceramic reinforced polymer that gives this product exciting new performance. Can be used on rubber, metal, wood, glass, paper, plastics, and elastomers and fibre.

DIRECTIONS

Shake can vigorously before using
Apply to clean, dry surfaces
Hold can 5 – 10 inches from surface and spray a thin uniform coating
Spray should wet surface for effective bonding
Do not overspray
Before re-coating remove old film with quality solvent degreaser

TECHNICAL DATA

Appearance	Dries Clear
Base Lubricant	PTFE
Temperature Range	48.9°C (120°F) to 148.9°C (300°F)

Dry Teflon Lubricant is available in this size:

Part # 21714 12 x 315 g aerosol

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com